

Product Spotlight

EPAR S Weigh bridge



PRODUCT DETAILS

EPAR S is a low viscosity lightly filled, high strength epoxy grout. EPAR S has very good mechanical properties and chemical resistance. EPAR S is non-shrink and has excellent adhesion to concrete, steel, stone, timber and many other materials.

Available with a cold cure hardener for use for temperatures down to 0°C and a fast cure hardener for quicker initial set.

EPAR S can be used for holding bolts or starter bars in concrete, grouting under machinery bearing plates, crane rails etc., high strength nosings for bridges and industrial floors, filling spalls, cracks and chips in concrete.

EPAR S is light grey in colour and pourable and will flow when used on floors or in joints or cracks.

Featured Project Details

LOCATION: TNL yard, Richmond, Nelson

DEVELOPER/BUILDER:
CONTRACTOR/PLACER: Reliance Engineering

ENGINEER/ARCHITECT: —

JOB DETAILS

Epoxy grouting under base plates for weigh bridge for new TNL yard in Nelson. Customer needed a product that was pourable, strong, non shrink and be usable where a cement based grout would be difficult to place. The advantage of Epar S is that it is self levelling and therefore flowed under the plate.

FRASER BROWN & STRATMORE LTD.

Products for Concrete and Construction

185 Rata Street, P O Box 35 136, Naenae, Lower Hutt, New Zealand.

Telephone (64 4) 567 8436, Fax (64 4) 567 7232, Email fbs@fbsltd.co.nz, Web www.fbsltd.co.nz



Products for Concrete and Construction